

## PolyPro™ 3000T Clear

<b>Media Type</b>	Label	✓	<b>Film Type</b>	Polyethylene	
	Receipt			Polyolefin	
	Tag			Polypropylene	✓
	Wristband			Polyester	
<b>Material Type</b>	Paper			Polyimide	
	Synthetic	✓		<b>Properties</b>	Cold Temperature
<b>Printing Technology</b>	Direct Thermal (no Ribbon Required)		Deep Freeze		
	Thermal Transfer (Ribbon Required)	✓	High Temperature		
<b>Adhesive Type</b>	Permanent	✓	Ultra High Temperature		
	Removable		High Tack		
	No Adhesive		Chemical Resistance		-
<b>Finish</b>	Matte		<b>Environment</b>	Indoor	✓
	Gloss	✓		Outdoor	

Note: Due to label transparency, barcode scannability depends on substrate colour.

### Additional Features

- Produces good quality text and barcodes with Zebra ribbons
- Adhesive complies with European food regulation EC 1935/2004, EU 10/2011 and BfR Recommendation XIV for direct contact with dry, moist and such kind of fatty foodstuffs which have a reduction factor of at least 2
- Adhesive complies with FDA 175.105 for direct contact with dry foodstuffs, or alternatively separated by a functional barrier
- Tear and water resistance
- BPA free
- Latex free adhesive

### Suggested Applications

- Document tracking
- Applications requiring the 'no label' look
- Chemical drum labelling and industrial product labelling
- Promotional labelling
- For use as a protective over-laminate
- Gloss materials are not suitable for fanfold applications

## Technical Specifications

	Description	Caliper
Facestock	Clear gloss polypropylene film	57 microns
Adhesive	Permanent acrylic adhesive	19 microns
Liner	61gsm glassine liner	54 microns
Total		130 microns $\pm$ 10%

**Recommended Zebra Printers:** Desktop, mid-range and high-performance thermal printers

**Recommended Zebra Ribbons:** 4800, 5095

**Minimum Application Temperature:** 5°C  
When the label is applied, the environment and surface should be above this temperature

**Service Temperature Range:** -20°C to 80°C  
Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range


**Recommended Storage Conditions:** 1 year duration when stored at 20°C to 25°C, at 40% to 50% RH  
Storage of product before use

**Expected Life Span in Application:** Indoor use, up to 1 year  
Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

## Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order sample roll SAMPLE65036.

<p>MSC Computer Vertriebs-Gesellschaft mbH Lötsch 39 41334 Nettetal Deutschland Telefon: 02153 - 95200 Email: <a href="mailto:info@msc-computer.de">info@msc-computer.de</a> URL: <a href="http://www.msc-computer.de">www.msc-computer.de</a></p> 
--