

Z-Band® Fun


Available
from stock
on ZipShip

Media Type	Label		Adhesive Type	Permanent	✓
	Receipt			Removable	
	Tag			No Adhesive	
	Wristband	✓	Environment	Indoor	✓
Material Type	Paper			Outdoor	✓
	Synthetic	✓	Properties	Cold Temperature	✓
Printing Technology	Direct Thermal (no Ribbon Required)	✓		Deep Freeze	✓
	Thermal Transfer (Ribbon Required)			High Tack	
Finish				Chemical Resistance	Mild
	Matte		Suggested Vertical	Healthcare	
	Gloss	✓		Hospitality	✓

Additional Features

- Available from stock in seven bright colours; red, yellow, blue, green, pink, orange and purple – 1 for every day of the week
- Excellent print quality down to 5mil narrow barcodes
- No ribbon required for direct thermal printing, therefore only one stock item needed
- Specifically designed for 1 day recreation applications
- Specifically developed varnish, to enhance the durability of the printed image
- Quick and easy to print and secure, with peel and seal tab closure
- Tamper evident slits and high performance permanent rubber adhesive to prevent fraud and enhance security, bands cannot be removed and reapplied
- Strong, tear resistant material
- Variable printing on demand, increases flexibility and reduces waste
- Latex free, BPA free, waterproof and resistant to smearing, abrasion, alcohol, mild cleansers and hand sanitizer gels

Suggested Applications

- Concerts and music festivals
- Corporate events
- Exhibitions and trade fairs
- Amusement and theme parks
- Sporting events
- Student identification for excursions
- Nightclubs
- Visitor and staff event identification
- Applications where cashless transactions or age verification is required

Technical Specifications

	Description	Caliper
Facestock	Gloss thermal imaging polypropylene	100 microns $\pm$ 10%
Adhesive Tab	Permanent rubber adhesive on kraft liner	90 microns $\pm$ 10%

Recommended Zebra Printers:

HC100, desktop, ZT200 Series and ZT410 thermal printers with the use of a 25mm media holder

Minimum Application Temperature:

When the label is applied, the environment and surface should be above this temperature

10°C

Service Temperature Range:

Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

-40°C to 70°C

Recommended Storage Conditions:

Storage of product before use

6 months duration when stored at 22° at 50% RH

Expected Life Span in Application:

Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

Indoor/outdoor use up to 1 day, test thoroughly in application before use

Recommended Darkness and Print Speed Settings:

ZPL Printers; Darkness: 22 Print Speed: 50mm/sec (2ips)
EPL Printers; Darkness: 13 Print Speed: 50mm/sec (2ips)
Printer settings automatically programmed in Zebra HC100 printer at 102mm/sec (4ips)

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this product, please contact your Supplies Specialist Representative.

MSC Computer Vertriebs-Gesellschaft mbH
Lötsch 39
41334 Nettetal
Deutschland
Telefon: 02153 - 95200
Email: info@msc-computer.de
URL: www.msc-computer.de

