

XENON™ ULTRA 1960 & 1962

Handheld Barcode Scanners

Accessories Guide

Honeywell

TABLE OF CONTENTS

- 3 Power options
- 4 Access points, charge and communication bases
- 5 Power supplies
- 6 Cables
- 7 Stands

POWER OPTIONS



BAT-SCN11

Lithium-ion Battery

Smart battery: Lithium-ion battery for Xenon™ Ultra 1962 Bluetooth® scanners.



Black: BAT-SCN11WC
White: BAT-SCN11WCHC

Lithium-Ion Battery – Contactless

Smart battery: Lithium-ion battery for Xenon Ultra 1962 contactless Bluetooth scanners.



SUPCAP-SCN11

Battery-Free Supercapacitor

Battery-free super capacitor for Xenon Ultra 1962 battery-free Bluetooth scanners.



Black: SUPCAP-SCN11WC
White: SUPCAP-SCN11WCHC

Battery-Free Supercapacitor – Contactless

Battery-free Super capacitor for Xenon Ultra 1962 battery-free contactless Bluetooth scanners.



MB4-BAT-SCN11*

4-Bay Battery Charger

4-Bay Battery Charger for Xenon Ultra 1962g/h and Granit Ultra, Kit includes (BAT-SCN11-CUP), Dock and Power Supply (12V3A), No Power Cord



BAT-SCN11-CUP

Cup for 4-Bay Battery Charger

Cup for 4-Bay Battery Charger MB4-BAT-SCN11

* When appended with a regional suffix such as NA or EU, the kit includes the corresponding regional power cord

ACCESS POINTS, CHARGE AND COMMUNICATION BASES



AP-010BT-07N

Bluetooth Access Point

Access point for scanners. Class 2 Bluetooth, 10m (33'), RS232/USB/KBW/IBM (cable sold separately).



AP-010BT-HC

Bluetooth Access Point - Healthcare

Access point for scanners. Class 2 Bluetooth, 10m (33'), RS232/USB/KBW/IBM (cable sold separately).



CCB-U00-H-KIT

Contactless:
CCB-U00-H-WCKIT

Xenon Ultra Charge and Communication Vertical Base Kit – Healthcare

Presentation charge and communication base, Class 1100M / Class 2 10M Bluetooth, 7 scanners can be connected, RS232/USB/KBW host interfaces (cables sold separately), white, disinfectant ready anti-microbial housing.

Enable Charge only mode: **BASLNKO**.



CCB-U00-G-KIT

Contactless:
CCB-U00-G-WCKIT

Xenon Ultra Charge and Communication Vertical Base Kit – General Purpose

Presentation charge and communication base, Class 1100M / Class 2 10M Bluetooth, 7 scanners can be connected, RS232/USB/KBW host interfaces (cables sold separately), black, disinfectant ready housing.

Enable Charge only mode: **BASLNKO**.



1962H-CUP-INS5

CCB Healthcare Insert

1962H white plastic insert in disinfectant ready housing to better stabilize scanner when subjected to turbulent movement



General Purpose (Black):
CCB-U00-G

Healthcare (White):
CCB-U00-H

Xenon Ultra Charge and Communication Presentation Universal Base Only

1962 Charge and Communication universal base for use charging cup of presentation CCB.



CCB-ULTRA-HORIZ-HC

Contactless Version:
CCB-ULT-HORIZ-HCWC

Xenon Ultra Charge and Communication Horizontal Base – Healthcare

Desktop/Wall mount charge and communication base, class 1100M/class 2 10M Bluetooth®, white, disinfectant ready anti-microbial housing.



CCB-ULTRA-HORIZ-GP

CCB-ULT-HORIZ-GPWC

Xenon Ultra Charge and Communication Horizontal Base – General Purpose

Desktop/Wall mount charge and communication base, class 1100M/class 2 10M Bluetooth, black, disinfectant ready housing.



General Purpose (Black) Battery Cup: 1962G-BAT-CUP

Contactless Cup: 1962G-WC-CUP

Healthcare (White) Battery Cup:

1962H-BAT-CUP Contactless Cup: 1962H-WC-CUP

Xenon™ Ultra Charge and Communication Presentation Cup Only

1962 Charge and Communication Cup for use with universal presentation base.

POWER SUPPLIES

For Xenon Ultra 1960 Corded Scanner ONLY



46-00525-6

Power Supply – NA Plug

Power Supply: NA plug,
1.0A @ 5.2V DC, 90-
255V AC @ 50-60Hz.



46-00526

Power Supply – EU Plug

Power Supply: EU plug,
1.0A @ 5.2V DC, 90-
255V AC @ 50-60Hz.



46-00528

Power Supply – AU Plug

Power Supply: AU plug,
1.0A @ 5.2V DC, 90-
255V AC @ 50-60Hz.



46-00529

Power Supply – CN Plug

Power Supply: CN plug,
1.0A @ 5.2V DC, 90-
255V AC @ 50-60Hz.

For Xenon Ultra 1960 & 1962 Scanners



46-00535-6

Power Supply –NA Plug

Power Supply: NA plug,
3.0A @ 5V DC, 100-
240V AC @ 50-60Hz.



46-00536-6

Power Supply – EU Plug

Power Supply: EU plug,
3.0A @ 5V DC, 100-
240V AC @ 50-60Hz.



46-00537-6

Power Supply – AU Plug

Power Supply: AU plug,
3.0A @ 5V DC, 100-
240V AC @ 50-60Hz.




46-00538-6


Power Supply – CN Plug

Power Supply: CN plug,
3.0A @ 5V DC, 100-
240V AC @ 50-60Hz.

Power supplies for cabled connections



Power supplies for charge/communication bases



CABLES

CBL-020-300-C00	CBL-120-300-C00	CBL-220-300-C00	CBL-420-300-C00	CBL-MAG-300-S00
RS-232 Power Cable Cable: RS232(5V signals), black, DB9 Female, 3m (9.8'), coiled, 5V external power with option for host power on pin 9, w/o ferrite.	RS-232 Power Cable Cable: RS-232C (+/-12V signals), black, DB9 Female, 3 m (9.8 ft), coiled, 5V external power with option for host power on pin 9.	RS-232 Power Cable Cable: RS-232 (+5V signals), black, DB9 Male, 3 m (9.8ft), coiled, external power with option for host power on pin 9 for connection to Wincor Beetle™.	RS-232 Power Cable Cable: RS-232 (5V signals), Honeywell Bioptic Stratos™ Aux, black, 10 pin modular, 3m (9.8 ft), coiled, host power possible (dependent upon scanner and Stratos models).	RS-232 Power Cable Cable: RS-232 (5V signals), Magellan™ Aux Port, black, 10 pin modular, 3 m (9.8 ft), straight, external power with option for host scanner power.
CBL-500-500-C00	CBL-500-500-S00	CBL-500-400-C00-01	CBL-500-150-S00	CBL-500-300-C00
USB Power Cable Cable: USB, black, Type A, 5m (16.4'), coiled, 5V host power, w/o ferrite.	USB Power Cable Cable: USB, black, Type A, 5m (16.4'), straight, 5V host power, w/o ferrite.	USB Power Cable Cable: USB, black, Type A, 4m (13.1'), coiled, 5V host power, w/o ferrite.	USB Power Cable Cable: USB, black Type A, 1.5m (5'), straight, 5V host power, w/o ferrite.	USB Power Cable Cable: USB, black, Type A, 3m (9.8ft), coiled, 5V host power.
CBL-500-300-S00	50177360-002	CBL-720-300-C00	CBL-800-300-C00	CBL-500-120-S00-HS
USB Power Cable* Cable: USB, black, Type A, 3 m (9.8'), straight, 5V host power.	USB Power Cable** Cable: USB, Type A, 2.7M (8.8'), straight, 5V host power.	Keyboard Wedge Power Cable Cable: KBW, black, PS2, 3m (9.8'), coiled, 5V external power with options for host power, w/o ferrite.	USB Power Cable, Type C Cable: USB Type C, black, 3m (9.8'), coiled, 5V host power, w/o ferrite.	USB Power Cable, High Speed Cable: USB, Type A, black, 1.2m (3.9'), 5V host power, w/o ferrite.

* Cable shipped with Xenon Ultra 1960 kit SKUs.

** Cable shipped with Xenon Ultra 1962 Kit SKUs.

STANDS



STND-22F00-016-6

Xenon™ Ultra 1960 Stand – Flexible Presentation Stand

Stand: gray, 22cm (9 in) height, flexible rod, large oval weighted base, Xenon Ultra 1960 cup.



STND-22F00-001-6

Xenon XP 1950 Stand – Flexible Presentation Stand

Stand: gray, 22 cm (9 in) height, flexible rod, large oval weighted base, Xenon 1900/1950 cup.

Use **PAPTPR** to configure your Xenon Ultra 1960 to utilize this legacy stand for presentation mode scanning.

For more information

automation.honeywell.com

Honeywell Industrial Automation

855 South Mint Street

Charlotte, NC 28202

800-582-4263

www.honeywell.com

Xenon and Stratos are trademarks or registered trademarks of Honeywell International Inc.

Bluetooth is a trademark or registered trademark of Bluetooth SIG, Inc.

Magellan is a trademark or registered trademark of Datalogic S.p.A.

All other trademarks are the property of their respective owners.

Xenon Ultra 1960 & 1962 Accessories Guide | A4 | Rev B | 01/26
© 2026 Honeywell International Inc.

Honeywell